

SUPER PLATINUM TRTL-60X6





SUPER PLATINUM TRTL-60X6

U.L. APPROVED TRTL-60X6.

SUPER PLATINUM by ISM is the only safe in the world which is U.L. approved for the TRTL-60X6 standard.

ISM's top of the line maximum burglary resistant security safe. SUPER PLATINUM was created as a result of ISM's conviction to create the world's best high security safe at a reasonable price.

Special Features: 2 hour, 350°F factory fire rating.

Body & Door: Multi-layered structure that combines outer and inner steel plates, reinforced steel bars and a monolithic casting of Alchronite, ISM's patented torch and drill resistant composite material, embedding a layer of ISM's patented anti-penetration alloy grid.

Bolts & Locking Mechanisms: Three-way active boltwork. Double-action locking mechanism. Glass plate relocking protection on all locks.

Locks: Two UL approved locks. Mechanical or digital combination lock and a high security key lock.

Interior Fitting: Adjustable removable shelves. A hole at the back of the safe for alarm system connection - optional.



Multi Layered 3 Structure



٩<u>ق</u>،



井



Specifications

opeemeations	SP 29	SP 38	SP 58	SP 68	SP 70
Outside Dimensions H / W / D	39/36/31	47/37/31	68/39/31	78/42/31	79/49/39
Inside Dimensions H / W / D	29/26/18	37/28/18	58/29/18	68/32/18	70/39/25
Est. Weight (Lbs)	2166	2565	3420	4047	5016
Volume (Cu. Ft)	7.9	10.7	17.5	22.7	39.8
Wall Thickness (inches)	4.8	4.8	4.8	4.8	4.8
Door Thickness (inches)	4.75	4.75	4.75	4.75	4.75
Special Alloy Grid	+	+	+	+	+
Torch Resistant Alloy	+	+	+	+	+
Fire Resistant (Hours)	2	2	2	2	2
Shelves	1	1	2	3	4
Number of Bolts	10	12	16	16	16
Bolt's Diameter (inches)	1.6	1.6	1.6	1.6	1.6
Mechanical Combination Lock	+	+	+	+	+
Digital Combination Lock	Optional	Optional	Optional	Optional	Optional
High Security Key Lock	+	+	+	+	+

* Weight Tolerance 5%.

С B

Door Swing Projections & Aperture Dimensions


		SP 29	SP 38	SP 58	SP 68	SP 70
Α	Aperture	21.9	22.8	25	28	34.9
в	Door Swing - 180°	62	64	68.3	73.8	87.6
С	Door Swing - 90°	62.4	63.6	65.7	68.7	82.5

* Add 3.25" to outside depth for Pull-Handle.



- Left Swing Optinal No charge
- · Preparation (only) for movement time-lock No charge By Request
- Custome interior secured compartments By Request

Additional shelves - By Request









ISM MAGEN GOLDMAN SAFES ENCLOSURE LTD 3 HaOdem Street, Barkan Industrial Zone, Israel 44820 | Tel: +972-3-9068839 Fax: +972-3-9068894 | Email: ism@ism-safes.co.il | Web: www.ism-safes.co.il

