



SUPER TREASURY TRTL-30X6



SUPER TREASURY TRTL-30X6

U.L. APPROVED TRTL-30X6

Super strong, six-sided protection against concentrated attacks with mechanical and electrical tools and oxy-acetylene torches.

Special Features: 2 hour, 350°F factory fire rating.

Body & Door: Multi-layered structure that combines outer and inner steel plates, reinforced steel bars and a monolithic casting of Alchrontite, ISM's patented torch and drill resistant composite material, embedding a layer of ISM's patented anti-penetration alloy grid.

Bolts & Locking Mechanisms: Three-way active boltwork. Double-action locking mechanism. Glass plate relocking protection on all locks.

Locks: Two UL approved locks. Mechanical or digital combination lock and a high security key lock.


Interior Fitting: Adjustable removable shelves. A hole at the back of the safe for alarm system connection - optional.



Specifications

	ST 29	ST 33	ST 44	ST 55	ST 64	ST 68	ST 68W
Outside Dimensions H / W / D	38/28/29	42/31½/33	53/31½/33	63½/31½/36	72/31½/36	77/40/32½	77/45/39½
Inside Dimensions H / W / D	29/19/16	33/23/20	44/23/23	55/23/23	64/23/23	68/31/19	68/36/26
Est. Weight (Lbs)	2310	2893	3568	4132	4756	5443	6655
Volume (Cu. Ft)	5.3	8.8	13.4	16.8	19.4	23.3	37.1
Wall Thickness (inches)	4.25	4.25	4.25	4.25	4.25	4.25	4.25
Door Thickness (inches)	4.25	4.25	4.25	4.25	4.25	4.25	4.25
Special Alloy Grid	+	+	+	+	+	+	+
Torch Resistant Alloy	+	+	+	+	+	+	+
Fire Resistant (Hours)	2	2	2	2	2	2	2
Shelves	2	2	3	3	3	4	4
Number of Bolts	10	10	12	16	16	16	16
Bolt's Diameter (inches)	1.6	1.6	1.6	1.6	1.6	1.6	1.6
Mechanical Combination Lock	+	+	+	+	+	+	+
Digital Combination Lock	Optional	Optional	Optional	Optional	Optional	Optional	Optional
High Security Key Lock	+	+	+	+	+	+	+

* Weight Tolerance 5%.



Door Swing Projections & Aperture Dimensions


	ST 29	ST 33	ST 44	ST 55	ST 64	ST 68	ST 68W
A Aperture	15.75	19.15	19.15	19.15	19.15	27.65	32.55
B Door Swing - 180°	49.2	55.9	55.9	55.9	55.9	74.2	82.9
C Door Swing - 90°	53.55	61	63.75	63.75	63.75	69	81.1

* Add 3.25" to outside depth for Pull-Handle.

Add Ons:

- Left Swing - Optinal - No charge
- Preparation (only) for movement time-lock - No charge - By Request
- Custome interior secured compartments - By Request
- Additional shelves - By Request

Colors:



ISM MAGEN GOLDMAN SAFES ENCLOSURE LTD

3 HaOdem Street, Barkan Industrial Zone, Israel 44820 | Tel: +972-3-9068839

Fax: +972-3-9068894 | Email: ism@ism-safes.co.il | Web: www.ism-safes.co.il



SAFE SINCE 1914