



BULLION TL-30



BULLION TL-30

U.L. APPROVED TL-30

High protection against concentrated attacks with mechanical and electrical tools.

Special Features: 2 hour, 350°F factory fire rating.

Body & Door: Multi-layered structure that combines outer and inner steel plates enclosing a monolithic casting of specialized concrete mixed with ISM's unique anti-penetration composite material. The door is reinforced with ISM's patented anti-penetration alloy grid, providing high protection against concentrated attacks with mechanical and electrical tools.

Bolts & Locking Mechanisms: Three-way active boltwork. Double-action locking mechanism. Glass plate relocking protection on all locks.

Locks: Two UL approved locks. Mechanical or digital combination lock and a high security key lock.


Interior Fitting: Adjustable removable shelves. A hole at the back of the safe for alarm system connection - optional.



Specifications

| | BU 18 | BU 25 | BU 35 | BU 45 | BU 55 | BU 60 | BU 68 | BU 72 |
|------------------------------|----------|----------|----------|----------|----------|----------|----------|----------|
| Outside Dimensions H / W / D | 25/21/24 | 32/25/28 | 42/28/32 | 52/28/32 | 62/28/32 | 67/28/32 | 75/38/32 | 79/43/37 |
| Inside Dimensions H / W / D | 18/14/12 | 25/18/16 | 35/21/20 | 45/21/20 | 55/21/20 | 60/21/20 | 68/31/20 | 72/36/26 |
| Est. Weight (Lbs) | 992 | 1499 | 2337 | 2800 | 3175 | 3461 | 4938 | 6040 |
| Volume (Cu. Ft) | 1.8 | 4.1 | 8.3 | 10.7 | 13.1 | 14.3 | 24.1 | 38.7 |
| Wall Thickness (inches) | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 |
| Door Thickness (inches) | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 | 3.55 |
| Special Alloy Grid | + | + | + | + | + | + | + | + |
| Fire Resistant (Hours) | 2 | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Shelves | 1 | 1 | 2 | 2 | 3 | 3 | 3 | 4 |
| Number of Bolts | 8 | 10 | 10 | 12 | 16 | 16 | 16 | 16 |
| Bolt's Diameter (inches) | 1.6 | 1.6 | 1.6 | 1.6 | 1.6 | 1.6 | 1.6 | 1.6 |
| Mechanical Combination Lock | + | + | + | + | + | + | + | + |
| Digital Combination Lock | Optional | Optional | Optional | Optional | Optional | Optional | Optional | Optional |
| High Security Key Lock | + | + | + | + | + | + | + | + |

* Weight Tolerance 5%.



Door Swing Projections & Aperture Dimensions


| | BU 18 | BU 25 | BU 35 | BU 45 | BU 55 | BU 60 | BU 68 | BU 72 |
|----------------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| A Aperture | 14 | 18 | 21 | 21 | 21 | 21 | 31 | 36 |
| B Door Swing - 180° | 36.6 | 44.9 | 50.8 | 50.8 | 50.8 | 50.8 | 65.4 | 81.5 |
| C Door Swing - 90° | 42.7 | 51.2 | 57.9 | 57.9 | 57.9 | 57.9 | 65.2 | 75.2 |

* Add 3.25" to outside depth for Pull-Handle.

Add Ons:

- Left Swing - Optional - No charge
- Preparation (only) for movement time-lock - No charge - By Request
- Custom interior secured compartments - By Request
- Additional shelves - By Request

Colors:



ISM MAGEN GOLDMAN SAFES ENCLOSURE LTD

3 HaOdem Street, Barkan Industrial Zone, Israel 44820 | Tel: +972-3-9068839
 Fax: +972-3-9068894 | Email: ism@ism-safes.co.il | Web: www.ism-safes.co.il



SAFE SINCE 1914