



PROTECTOR TL-15



PROTECTOR TL-15

ISM FACTORY RATING TL-15



Special Features: 2 hour, 350°F factory fire rating.

Body & Door: Multi-layered structure that combines outer and inner steel plates enclosing a monolithic casting of specialized concrete mixed with ISM's unique anti-penetration composite material. The door is reinforced with ISM's patented anti-penetration alloy grid, providing high protection against concentrated attacks with mechanical and electrical tools.

Bolts & Locking Mechanisms: Three-way active boltwork. Double-action locking mechanism. Glass plate relocking protection on all locks.

Locks: Two UL approved locks. Mechanical or digital combination lock and a high security key lock.

Interior Fitting: Adjustable removable shelves. A hole at the back of the safe for alarm system connection - optional.



Glass Plate Relocking Protection



Multi Layered Structure



Reinforced Bolt Cylinders



4-Way Bolts Engagement



Special Alloy Grid




Double Locking Protection

Specifications

	PR 18	PR 25	PR 35	PR 45	PR 55	PR 60	PR 68	PR 72
Outside Dimensions H / W / D	24/20/23	30/24/27	41/27/31	51/27/31	61/27/31	66/27/31	74/37/31	78/42/37
Inside Dimensions H / W / D	18/14/12	25/18/16	35/21/20	45/21/20	55/21/20	60/21/20	68/31/20	72/36/26
Est. Weight (Lbs)	838	1279	1874	2205	2480	2734	3638	4564
Volume (Cu. Ft)	1.8	4.2	8.5	10.9	13.4	14.5	24.6	39
Wall Thickness (inches)	2.95	2.95	2.95	2.95	2.95	2.95	2.95	2.95
Door Thickness (inches)	2.75	2.75	2.75	2.75	2.75	2.75	2.75	2.75
Special Alloy Grid	+	+	+	+	+	+	+	+
Fire Resistant (Hours)	2	2	2	2	2	2	2	2
Shelves	1	2	2	2	3	3	3	3
Number of Bolts	8	10	10	12	16	16	16	16
Bolt's Diameter (inches)	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
Mechanical Combination Lock	+	+	+	+	+	+	+	+
Digital Combination Lock	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
High Security Key Lock	+	+	+	+	+	+	+	+

* Weight Tolerance 5%.



Door Swing Projections & Aperture Dimensions


	PR 18	PR 25	PR 35	PR 45	PR 55	PR 60	PR 68	PR 72
A Aperture	14	18	21	21	21	21	31	36
B Door Swing - 180°	36.7	44.6	50.5	50.5	50.5	50.5	71.2	81
C Door Swing - 90°	40.8	48.9	55.8	55.8	55.8	55.8	66.6	77

* Add 3.25" to outside depth for Pull-Handle.

Add Ons:

- Left Swing - Optional - No charge
- Preparation (only) for movement time-lock - No charge - By Request
- Custom interior secured compartments - By Request
- Additional shelves - By Request

Colors:



ISM MAGEN GOLDMAN SAFES ENCLOSURE LTD

3 HaOdem Street, Barkan Industrial Zone, Israel 44820 | Tel: +972-3-9068839
Fax: +972-3-9068894 | Email: ism@ism-safes.co.il | Web: www.ism-safes.co.il



SAFE SINCE 1914