



ULTRA TAULT TL-30X6



ULTRA VAULT TL-30X6

U.L. APPROVED TL-30X6. The first safe to receive Underwriters Laboratories (U.L.) label TL-30X6.

Six-sided protection against concentrated attacks with mechanical and electrical tools. The same high quality construction as the highest rated safes at an affordable price.

Special Features: 2 hour, 350°F factory fire rating.

Body & Door: Multi-layered structure that combines outer and inner steel plates, reinforced steel bars and monolithic casting of specialized concrete mixed with ISM's unique anti-penetration composite material. Both body and door are reinforced with ISM's patented anti-penetration alloy grid.

Bolts & Locking Mechanisms: Three-way active boltwork. Double-action locking mechanism. Glass plate relocking protection on all locks.

Locks: Two UL approved locks. Mechanical or digital combination lock and a high security key lock.


Interior Fitting: Adjustable removable shelves. A hole at the back of the safe for alarm system connection - optional.



Specifications

	UV 25	UV 34	UV 46	UV 59	UV 59D	UV 63	UV 68
Outside Dimensions H / W / D	32/26/28	41/27/30	53/27/30	66/27/30	66/27/35	70/39/30	75/43/38
Inside Dimensions H / W / D	25/19/16	34/20/18	46/20/18	59/20/18	59/20/23	63/32/18	68/36/26
Est. Weight (Lbs)	1818	2358	2844	3439	3836	4717	5400
Volume (Cu. Ft)	4.5	7.1	9.7	12.4	15.9	21	36.9
Wall Thickness (inches)	3.55	3.55	3.55	3.55	3.55	3.55	3.55
Door Thickness (inches)	3.55	3.55	3.55	3.55	3.55	3.55	3.55
Special Alloy Grid	+	+	+	+	+	+	+
Fire Resistant (Hours)	2	2	2	2	2	2	2
Shelves	1	2	2	3	3	3	4
Number of Bolts	8	10	12	16	16	16	16
Bolt's Diameter (inches)	1.6	1.6	1.6	1.6	1.6	1.6	1.6
Mechanical Combination Lock	+	+	+	+	+	+	+
Digital Combination Lock	Optional	Optional	Optional	Optional	Optional	Optional	Optional
High Security Key Lock	+	+	+	+	+	+	+

* Weight Tolerance 5%.



Door Swing Projections & Aperture Dimensions


	UV 25	UV 34	UV 46	UV 59	UV 59D	UV 63	UV 68
A Aperture	19	20	20	20	20	32	36
B Door Swing - 180°	48	50.3	50.3	50.3	50.3	75.7	84
C Door Swing - 90°	52.2	55.3	55.3	55.3	60.5	68.4	80.6

* Add 3.25" to outside depth for Pull-Handle.

Add Ons:

- Left Swing - Optinal - No charge
- Preparation (only) for movement time-lock - No charge - By Request
- Custome interior secured compartments - By Request
- Additional shelves - By Request

Colors:



ISM MAGEN GOLDMAN SAFES ENCLOSURE LTD

3 HaOdem Street, Barkan Industrial Zone, Israel 44820 | Tel: +972-3-9068839
Fax: +972-3-9068894 | Email: ism@ism-safes.co.il | Web: www.ism-safes.co.il



SAFE SINCE 1914